

Cement Stabilization for Managing Oil-Impacted Dredged Material Planned for Disposal in a CDF



Presented by

Steve Cappellino and Shelly Anghera, Anchor QEA, LLC
Dylan Porter and Matt Arms, Port of Long Beach

2014 Pacific WEDA Fall Conference
Seattle, Washington

October 23, 2014

Middle Harbor Redevelopment Project (Existing)




- Consolidate two irregular older facilities into one efficient, 345-acre, rectangular-shaped terminal

Middle Harbor Redevelopment Project (Completed)



- Construction will occur in two phases, each with multiple stages, over a 10-year period


The Middle Harbor Redevelopment Site



P:\14465-01_Pac E Terminal Redevelopment\7_Bidg Information\CAD\USCE Permit\W025 Exhibit D28 East Basin Disposal Fig 1 20140210.dwg Feb 11, 2014 - 10:58am

Oil Timeline of Events

- April 2013
 - Oil sheen first encountered along D28 cut
 - Stop work ordered by the Port
 - Developed BMPs with Coast Guard to manage sheen
 - Absorbent pads and booms in water and barge
 - Disposal to fill site behind containment dike after “cleaning” to keep isolated from F berth
 - Dredging resumed within 7 days
 - PTS Services added to construction team to provide 24/7 services during dredging of D28



Oil Timeline of Events



- April 2014
 - Dredging D28 cut Manson encountered free product oil
 - Old, heavy, weathered material mixed with 1,100 cy of sand
 - Exceeded capabilities of existing BMPs
 - Dredging suspended immediately
 - Port CM started looking for solutions

BMPs Considered

- Potential options considered removing the oil from the barge or hauling to a waste facility for disposal
 - Removal of oil using a vacuum truck
 - Ineffective after 3 days of pumping and remixing in barge
 - Costs and schedule delays not manageable
 - Upland disposal
 - Required permitting and constructing an offloading area
 - Securing a contract for waste disposal
 - Loss of sandy material from the fill site
 - Estimated costs of \$300,000 per barge for disposal
 - Binding of oil with amendments

Oil Amendment

- Previously developed and demonstrated for CSTF
- Project needs during active construction
 - Cost-effective amendment
 - Constructible and acceptable by the contractor
 - Minimal schedule impacts
 - Oil remains bound after placement in CDF; however, could not solidify in barge
 - Acceptable to the agencies



Bench-Scale Pilot Study

- Study objectives
 - Use cement- and non-cement-based additives
 - Multiple test concentrations
 - Simulate barge mixing using excavator or clamshell bucket
 - Test for leaching in seawater
 - Consider potential for delays between treatment and disposal



Bench-Scale Pilot Study

- Study design
 - Sample preparation
 - Used 5-gallon HDPE buckets
 - Each contained approximately 6 inches of dredged sediment
 - 1-3 inches of overlying water
 - Layer of oil
 - Binding agents
 - Portland cement
 - Crudesorb (CETCO Corp.)
 - Concentrations ranging from 2-10%
 - Monitor for 48 hours



Bench-Scale Pilot Study

- 2% by weight, dry Portland cement (Type II/V)
- 5% by weight, dry Portland cement (Type II/V)
- 3% by weight, dry Portland cement (Type II/V), and increased overlying water levels to between 2 and 4 inches to evaluate the need for dewatering prior to mixing in the amendment
- 10% by weight, dry Crudesorb
- 5% by weight, dry Crudesorb
- 4% by weight, Portland cement (Type II/V) as a slurry, minimal overlying water



Bench-Scale Pilot Study Results

- Both 3% and 5% Portland cement amendments sufficiently bound oil
- Maintained binding ability for 48 hours
- Amended material combined with raw seawater to simulate the release of amended material produced no sheen
- 4% cement as a slurry was easier to mix and retained binding capacity
- Removing overlying water prior to amendment resulted in less cement to achieve binding
- None of the treatments below 5% resulted in solidified product

Bench-Scale Pilot Study Results



Prior to
Amendment



4% Cement Slurry
Immediately After
Mixing



24 hours Post
Amendment with
Seawater

Bench-Scale Pilot Study Results



5% Crudesorb
Immediately After Mixing



5% and 10% Crudesorb
24 hours After Mixing

POLB Middle Harbor Sediment Amendment
Full-Scale Field Pilot Study





Full-Scale Field Pilot Study

- 100 cy of cement slurry was added to 1,100 cy of impacted sediment
 - 3% by weight of cement
- Sediment and cement slurry was mixed
 - 7-cy clamshell bucket
 - 30 to 60 minutes























Full-Scale Field Pilot Study

- After mixing, five samples collected from both ends of barge
 - Sent to laboratory for elutriate analysis
- Barge was delivered to East Basin fill area
 - BMPs in place prior to barge arrival
 - Oil response team immediately mobilized for light oil sheen





NOTES

1. VOLUME OF ROCK (-20) = 44,750 CY
2. CAPACITY TO -22' = 32,650 CY
3. F-PIT CAPACITY LOSS = 14,950 CY



PIER E TERMINAL REDEVELOPMENT SLIP NO. 1 FILL D28 CONTAINMENT AREA FOR OIL IMPACTED MATERIAL OPTION A	Sheet 1 of 2
----------------------------------------------------------------------------------------------------------------------------------------	--------------

Full-Scale Field Pilot Study



- Water quality monitoring
 - 24 hour post placement
- Visual monitoring
 - For 48 hours post placement



Pilot Study Analytical Results

- Elutriate testing on amended sediment
- Water column monitoring
 - Standard monitoring at project boundary
- Metals, PAHs, total petroleum hydrocarbons
- All measured values below standards

Full-Scale Field Pilot Study – Round 2



Full-Scale Field Pilot Study – Round 2



Full-Scale Field Pilot Study – Round 2



Full-Scale Field Pilot Study – Round 2



Full-Scale Field Pilot Study – Round 2



Full-Scale Field Pilot Study – Round 2



Full-Scale Field Pilot Study Conclusions

- Amending dredged material with cement slurry was effective for binding oil within sediments
- Minor oil sheen observed after treatment was consistent with routine disposal events
- Water quality monitoring and elutriate testing confirm the successful binding of oily materials
- Removing standing water prior to treatment most effective
- Costs per barge for cement treatment is \$25,000 plus equipment rental

Questions/Discussion

