


NATIONAL DREDGING QUALITY MANAGEMENT (DQM) PROGRAM

WEDA MIDWEST CHAPTER

MARCH 10, 2017

OMAHA, NE

**VERN GWIN, PROGRAM DIRECTOR
NATIONAL DQM CENTER**



PRESENTATION OUTLINE

- **PROGRAM STATUS/ADVANCEMENTS**
- **CURRENT SIGNIFICANT ACTIVITIES**
- **FUTURE OBJECTIVES**



BUILDING STRONG®

PROGRAM STATUS

SINCE LAST YEAR....

- **V2.9 WAS RELEASED**
- **NEW SECURITY ACCESS**
- **GOV PLANT PIPELINE MONITORING**
- **AUTOMATED ULLAGE IMPLEMENTATION**
- **ODESS PROGRAM IMPLEMENTATION**



2017

- Private Pipeline Monitoring
- New Customers/More Customer Service
- ODESS Implementation
- BOEM Dredge Intensity Model
- Dev
 - ▶ V2.9, V3.0, Portal, ACS, Desktop tools, Management Tools



More 2017

- Technical Advancements
 - ▶ Cloud, Machine Learning, OSIsoft
- Personnel Changes
- Alaska Analysis
- Hopper Dredge Utilization Study
- DQM, DIS and RMS
- Revising Specs for Non-Nuclear Density Meters



NEW V2.9 DQM VIEWER



BUILDING STRONG®

SECURITY REQUIREMENTS

- **AS2 REQUIREMENTS FOR DATA WEB SERVICES**
 - ▶ **DATA TRANSMITTAL**
 - ▶ **USER ACCESS**
- **SECURITY MATRIX ROLES AND ACCESS**
 - ▶ **PASSWORD ACCESS – CONTRACTOR ACCESS**



PIPELINE IMPLEMENTATION

- HEAD QUARTERS IMPLEMENTATION GUIDANCE APRIL 2014
- PILOT MONITORING USACE DREDGING PLANTS IN SUMMER 2015
- INDUSTRY SPEC VERSIONS (CURRENTLY RECENT ADDRESSING COMMENTS)
- MARCH 2016 HEADQUARTERS DIRECTED DQM TO IMPLEMENT MONITORING ON >18"



National Dredging Quality Management Program (DQM)

Pipeline Data Flow Sensor-Based Parameters (per Compliance Specification)



Pump Sensors

- Pump Vac
- Pump Press
- Density
- Velocity



Position Sensors

- Position
- Heading
- Vert Correction (Tide)
- CH Depth



Discharge Sensors

- (radio link)
- Discharge Position
- Discharge Elevation
- Discharge Heading

Notes

*Dredge Positioning Computer—Data is compiled and converted to JSON format

**DQM Onboard Computer—Minimum Specifications

CPU: Intel/AMD processor; 3 GHz (non-overclocked) clock speed

Hard Disk: 250 GB; internal

RAM: 2 GB

Ethernet Adapter: 10/100 Mbps internal network card; RJ-45 connector

Video Adapter: Supports 1024x768 resolution at 16-bit color depth

Monitor: 17" viewable display; supports 1024x768 resolution at 16-bit color depth

Keyboard: Standard 101-key

Mouse: Standard 2-button

CD-ROM Drive: 16X read speed/8X write speed

Ports: 2 free serial ports (standard 9-pin connectors); 1 free USB port

Cables: Cat-5 cable; standard RJ-45 plugs connecting the network adapter to the network hub; 1 spare cable

Software: Windows 7 Professional (fully licensed); any necessary manufacturer-provided drivers for the installed hardware



DQM ON-BOARD SOFTWARE (DQMOBS)

[illegible]

Currently Viewing


Plant Bill Holman
 Type Pipeline
 Project Project_Test_Bill_Holman
 Contract CONTRACT_TEST_BILL_
 Start Date 05/30/2012
 End Date 11/02/2015

PREV

NEXT

Selected Point

ADVANCE_DAILY null
 ADVANCE_HOURLY null
 ADVANCE_TOTAL null
 CH_DEPTH -12.29
 CH_HEADING 268.60
 CH_LATITUDE 37.072012
 CH_LONGITUDE -88.564571
 CH_RATE null
 CH_RPM 200.21
 CH_SWING null
 MSG_BUNDLE_ID 916206
 MSG_STATUS_ID undefined
 MSG_DATE 05/30/2012
 MSG_TIME 11:27:06
 OUTFALL_ELEVATION null
 OUTFALL_HEADING -19.90
 OUTFALL_LATITUDE 37.074674
 OUTFALL_LONGITUDE -88.562046
 PROD_CUMULATIVE 1074.30
 PROD_INSTANTANEOUS 11.30
 PROD_INTEGRATED null
 SLURRY_DENSITY 1.02
 SLURRY_VELOCITY 15.48
 SURVEY_DEPTH null
 SWING_CABLE_PSI_PORT 0
 SWING_CABLE_PSI_STBD 141.72
 TARGET_DEPTH null
 VERT_CORRECTION 302




100% 75% 50% 36% 25%

Zoom 1 Min 1 Hr 1 D All




Dredge Status

Pipe Length [insufficient Data]
 Boosters [WIP [insufficient Data]
 Effective Time [insufficient Data]
 Non-effective Time [insufficient Data]



— ADVANCE_DAILY
 — ADVANCE_HOURLY
 — ADVANCE_TOTAL
 — CH_DEPTH
 — CH_HEADING
 — CH_LATITUDE
 — CH_LONGITUDE
 — CH_RATE
 — CH_RPM
 — CH_SWING
 — OUTFALL_ELEVATION
 — OUTFALL_HEADING
 — OUTFALL_LATITUDE
 — OUTFALL_LONGITUDE
 — PROD_CUMULATIVE
 — PROD_INSTANTANEOUS
 — SLURRY_DENSITY
 — SLURRY_VELOCITY
 — SURVEY_DEPTH
 — SWING_CABLE_PSI_PORT
 — SWING_CABLE_PSI_STBD
 — TARGET_DEPTH
 — VERT_CORRECTION







Overview

- T&E Species Data Collection and Decision Making Tool in support of Operations and Dredging, starting with sea turtles, sturgeon
- Streamline T&E species data collection, processing, and reporting
- Reduction in premature project shut down
- Pilot Testing complete
- Full Implementation late 2016




Dredge Intensity Model


- ✓ Software tool which takes the results of the mathematical model and creates products compatible with prominent GIS applications
- ✓ Vessel transit tracks delineating areas of high traffic use
- ✓ Generation of relevant geospatial metadata for the product including processing history sections




Data Transformation




- Time spent at each location is calculated
- GPS locations are converted to UTM, and a grid is constructed
- Time per-location is accumulated within cells of a grid
- Values are normalized based on the cell size, final units are seconds per meter squared.




Westport Tracks & Dredging



Westport Heat Map



Google Earth Overlay



NEW NATIONAL DREDGING QUALITY MANAGEMENT DQM PORTAL



Search for Application



Certifications/QA



Administration



Reports



Plots



Export



Dashboard



Payments



DQM Viewer



Training



Tools



DQM Public Website



Question/Comments?



NATIONAL DREDGING QUALITY MANAGEMENT
DQM



BUILDING STRONG®



THE NATIONAL DREDGING QUALITY MANAGEMENT PROGRAM

The DQM Program is a partnership between the Corps and the dredging industry for automated monitoring of dredge activities.

Onboard sensors provide near-real-time data that allows for immediate response to emerging situations.

Districts can use the web-based DQM software to view, analyze, report on, and export dredging data.

The data can be used to improve business practice, ensure environmental compliance, and increase our understanding of dredging science and technology.

